



SPECIFICATION

Output: 113/136cc/min(50/60Hz)

Ratio: 1/11

Motor: 0.2kW AC100V/200V φ1
Rated Current: 4.1A(50Hz), 3.3A(60Hz

2.1A(50Hz), 1.7A(60Hz)

Discharge Pressure: Max 15.0MPa Pump Type: Double Plunger Usable Grease: NLGI No.0∼1

Container: 16kg Pail Can(Standard)

18kg Pail Can(Option)

Relief Pressure: 15.0MPa

Weight: 17.5kg

- · A portable grease pump with a handy gun.
- Simply attach it to the pail and it is ready to use!

Very easy to Install

Reduction of Running Cost

Extension of Machine Life

High cost-effectiveness with Low installation cost

■Special Feature

- * Since agitator blade is adopted instead of a follower plate, it is mush easier to replace the pail can.
- * Double plunger pump prevents air biting.
- * Trolleys make it easier to move around.

Air Relief Valve

Releases air due to air bites

SIGHT HOLES

The grease level can be checked by illuminating one side with a light.



Easy-to-operate grease gun



POWER SWITCH



HIGH PRESSURE HOSE $1/4 \times 5$ m

AGITATOR BLADE

The blade rotates to flatten the grease and increase suction efficiency.





Agitator blade levels the surface of grease.



•You can use up the grease to the bottom.



Easy to move with trolley *Option



Pressure Gauge *Option

Battery-driven type

Cartridge type or Filling type Nozzle tip with hydro coupling



Spray Nozzle *Option

Other Options for Single Lubrication



■Jumpet / KJP-1 Battery-driven single lubricator No plumbing or wiring required Operation interval and timing can be set Cartridge type prevents foreign substances

Shoulder belt is included as standard

■Cordless Electric Grease Gun / KBP-1-D2

Easy greasing with powerful pressure (21MPa)



